FVO-200RC

FVO-200RC42

FVNP-200RC

MODEL	FVO-200RC	FVO-200RC42	FVNP-200RC
Heat Capacity	185,000 btuh	185,000 btuh	200,000 btuh
Fuel Tank Capacity/Run Time	23 US Gallons / 17hrs	42 US Gallons / 35 hrs	External
Heater Dimensions/Weight	44 " x 27" x 48" / 350 lbs	51.5" x 27" x 48" / 425 lbs	43 1/4 " x 27" x 44" / 300 lbs
Heater Exchanger	16 Gauge 304 Stainless Steel	16 Gauge 304 Stainless Steel	16 Gauge 304 Stainless Steel
Fan Motor	2,600 CFM Ductable up to 150ft	2,600 CFM Ductable up to 150ft	2,600 CFM Ductable up to 150ft
Air Outlet/Inlet	Outlet - 1 x 12" Dia. or 1 x 16" Dia. Inlet - 1 x 12" Dia.	Outlet - 1 x 12" Dia. or 1 x 16" Dia. Inlet - 1 x 12" Dia.	Outlet - 1 x 12" Dia. or 1 x 16" Dia. Inlet - 1 x 12" Dia.
Wheels	12" Dia. Pneumatic Wheels 6" Lockable Caster Wheels	16" Dia. Flat Free Wheels	12" Dia. Pneumatic Wheels 6" Lockable Caster Wheels
Power Requirements	115V / 15Amp (6 Amp Draw)	115V / 15Amp (6 Amp Draw)	115V / 15Amp (6 Amp Draw)

FEATURES:

Proven Riello burner technology including nozzle pre-heater for cold weather start up and upgraded low temperature fuel pump.
Powerful backward incline blower provides ultra-quiet operation & low amperage, smart power indicator control and ductable up to 150FT.
Stackable frame allow for convenient transportation and storage.